

## **HUSH-WALL System**

### **Metal and Wooden Stud Walls**

Fix Hush-Bars to stud, horizontal at 450mm centres.

Install required thickness of Hush-Slab to cavity between studs.

Fit Hush-Isolation Tape to perimeter where the Hush-Wall boards will come into contact with floor, walls and ceiling.

Start at floor level and finish at ceiling level.

Cut off bottom overlap edge from wall board and overlap on end that will be adjacent to side wall.

Fit Hush-wall board at floor level to Hush-Bars, fixing into the bars only, with 32mm dry wall screws.

Work across the wall in a horizontal direction.

Continue with additional rows to complete the wall.

Ensure any gaps are filled with acoustic mastic.

Finish with scrim joints and plaster skim.

The remaining side of the wall should be upgraded with a second layer of 12.5mm plasterboard, fixed directly into the studwork.

### **Brick and Block Walls**

Fix Hush-Bars to the wall, horizontal at 450mm centres (drilled & plugged).

Install Hush-Slab 25 to wall, fitting tightly between the Hush-Bars.

Fit Hush-Isolation Tape to perimeter where the Hush-Wall boards will come into contact with floor, walls and ceiling.

Start at floor level and finish at ceiling level.

Cut off bottom overlap edge from wall board and overlap on end that will be adjacent to side wall.

Fit Hush-wall board at floor level to Hush-Bars, fixing into the bars only, with 32mm dry wall screws.

Work across the wall in a horizontal direction.

Continue with additional rows to complete the wall.

Ensure any gaps are filled with acoustic mastic.

Finish with scrim joints and plaster skim.

***Should you have any technical questions prior to or during installation, please call 0151 933 2026 for friendly and straightforward advice.***